

Brand: Hurricane
Engine: VW aircooled engine
Part Type: Connecting Rods
Center to Center Length: 136.96mm/5.392"
Big End Bore Diameter: 57.805mm/2.276"
Big End Width: 22.65mm/0.892"
Small End Bore Diameter: 22.005mm /0.866"
Small End Width: 24.70mm/0.972"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8"
Quantity :4pcs/set
Approximate Connecting Rod Weight: 540g/piece
Advertised Horsepower Rating: 800hp
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept


These rods are for VW aircooled engines ,machined from high strength 4340 steel material. Each rod are heat treated, magnafluxed and fully CNC machined for high strength , shot peened and polished for improved fatigue life, and honed to reach accurate sizes . Sold in sets of four pieces, and balanced weight sets +/- 1gram , you can look at the main sizes tolerance in our [official website](#) .

Per part of the rods finished completely , and they are available for genuine ARP2000 connecting rod bolts . But please kindly note , if you need the rods with genuine ARP bolts when placing order , please contact our staff first to check stock .





Hurricane also supply self-made connecting rods bolts , the tensile strength reach to 211829psi , the test report as below :



SGS


TEST REPORT

No. : GZMR120408793
 Date : May 09, 2012
 Page: 2 of 2

Test Result(s)
 Sample description: Metal part
 Test item : Tensile test
 Test method: With reference to ASTM F606-11a


Test item	Result
The maximum force, F _m (lbf)	18241
Tensile strength R _m (psi)	211820

Test photo:



3/8"-24TX1-1/4"
*****End of report*****

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions. This document is subject to the terms and conditions of the contract. It is the property of the Company and its confidentiality must be maintained. It is not to be distributed outside the Company's facilities. The Company's sole responsibility is to its Client and the document does not constitute part of a transaction. Any processing of it by any other organization under the transmission conditions. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Please refer to the sample shown in this test report refer only to the sample(s) tested and such sample(s) are labeled for 20 days only.



SGS
 Société Générale de Surveillance
 120408793

GZMR 0155923

Member of the SGS Group (SGS SA)



Both bolts has some difference between strength and price , you can view more details in [here](#) or contact out experienced staff directly .