

Brand: Hurricane
Engine: GM Air Cooled
Part Type: Connecting Rods
Center to Center Length: 142.24mm/5.600"
Big End Bore Diameter: 53.97mm /2.1248"
Big End Width: 22.65mm/0.8917"
Small End Bore Diameter: 22.005mm/0.8663"
Small End Width: 24.7mm/0.9724"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8 "
Approximate Connecting Rod Weight: 550g/piece
Advertised Horsepower Rating: 1000hp
Quantity: Sold as 8 pieces /set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

Inversion rods for GM air cooled engine Description

Hurricane H-Beam Chevy Air cooled connecting rods are made from 1-piece chromoly 4340 steel forging to ensure maximum strength and durability. Square shoulder design are common use at air cooled inversion series rods for higher horsepower. They are great update over stock rods.



[Hurricane Speed And Performance](#) air cooled performance connecting rod is ready to install or run on engine. Every piece of our conrods is shot blasted, honed and balance weighted. Hurricane GM air cooled connecting rods is sold in set of 8, the advise horsepower rating is 1000HP.



The Big end bore is machined on CNC advance machinery and honed on Sunnen Honing Machine. So the surface is very smooth and its precision is within 0.01mm after honing. Much more Hurricane Air cooled connecting rods bearing tag can fit OEM spec bearings.



For any help or more information, please call our helpline on +86 288 473 3371 or email in on marketing@hurricane-rod.com.cn to speak with one of our Qualified Staff.

Chevy Classic Automotive Picture

