

Brand: Hurricane
Engine: Nissan HR12*
Part Type: Connecting Rods
Center to Center Length: 130mm/5.118"
Big End Bore Diameter: 43.00mm/1.693"
Big End Width: 18.72mm/0.737"
Small End Bore Diameter: 18.97mm /0.747"
Small End Width: 18.72mm/0.737"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 5/16"
Approximate Connecting Rod Weight: 387g/piece
Advertised Horsepower Rating: 550hp
Quantity: Sold as 4 pieces /set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

Nissan HR12 H beam connecting rod is our newest rods which we are developing now ! Forged 4340 steel forgings with these specs:

1. material:40CrNiMoA heat treatment:HRC34-38
2. copper bush:QAL10-3-1.5
3. dowel:40Cr,HRC40-42
4. surface:Extra shot peened non machined surfaces
5. no note tolerance:+/-0.15
6. bolt torque:5/16-48N*M
7. packing:4pcs/set,balance weight +/-1g

All Nissan connecting rods we produced before, includes:

[**Nissan L18 L28 Conrods**](#)

[**Nissan 2.0 SR20DE SR20DET Conrods**](#)

[**Nissan 2.6 Skyline RB25/RB26DETT Conrods**](#)

[**Nissan CA16DE CA18DET Conrods**](#)

[**Nissan 350Z G35 VQ35 Conrods**](#)

[**Nissan QR25 Conrods**](#)

[**Nissan TB48 PATROL Conrods**](#)

[**Nissan 240SX-KA24DE Conrods**](#)

[**Nissan 300ZX-VG30DET Conrods**](#)

[**Nissan E15 Conrods**](#)

[**Nissan RB30 Conrods**](#)

Hurricane have decades of experience on designing and manufacturing racing connecting rods, and currently is known by more and more importers and purchasers around the world, such as USA, Canada, Australia, UK, Germany, France, Italy, Thailand, Singapore, Malaysia and so on.



Welcome to click [Nissan Connecting Rods](#) series to explore more details .

If you can not find the ones which you are looking for, please feel free to contact us.