Brand: Hurricane Engine: VW aircooled engine Part Type: Connecting Rods Center to Center Length: 136.96mm/5.392" Big End Bore Diameter: 57.805mm/2.276" Big End Width: 22.65mm/0.892" Small End Bore Diameter: 22.005mm /0.866" Small End Width: 24.70mm/0.972" Beam Style: H-beam Connecting Rod Bolt Diameter: 3/8" Quantity :4pcs/set Approximate Connecting Rod Weight: 540g/piece Advertised Horsepower Rating: 800hp Material: Forged 4340 steel Connecting Rod Finish: Shot-peened, Polished Pin: Bronze wrist pin bushings Wrist Pin Style: Floating Cap Retention Style: Cap screw Weight Matched Set: Yes ,Balanced +/- 1g Magnafluxed: Yes Private Label: Yes ,available Custom design: Yes, accept

These rods are for VW aircooled engines ,machined from high strength 4340 steel material. Each rod are heat treated, magnufluxed and fully CNC machined for high strength , shot peened and polished for improved fatigue life, and honed to reach accurate sizes . Sold in sets of four pieces, and balanced weight sets +/- 1gram , you can look at the main sizes tolerance in our official website.

Per part of the rods finished completely , and they are available for genuine ARP2000 connecting rod s bolts . But please kindly note , if you need the rods with genuine ARP bolts when placing order , pl ease contact our staff first to check stock .





Hurricane also supply self-

made connecting rods bolts , the tensile strengthe reach to 211829psi , the test report as below :

		No. 1 G2MR120408793 Date : May. 09, 2012 Page: 2 of 2	
Test Result(s) Semple description: Metal par Test flem: Tensile test Test method: With reference t			
Test to	-	Result	
The maximum fo Tensile strength		16241 211829	
FR			
	Market of rep	Ald'	



Both bolts has some difference between strength and price , you can view more details in $\frac{here}{here}$ or c ontact out experienced staff directly .