

Brand: Hurricane*
Engine: Honda H23
Part Type: Connecting Rods
Center to Center Length: 141.50mm/5.571"
Big End Bore Diameter: 51.01mm/2.008"
Big End Width: 23.75mm/0.935"
Small End Bore Diameter: 22.01mm /0.867"
Small End Width: 23.75mm/0.935"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8"
Approximate Connecting Rod Weight: 565g/piece
Advertised Horsepower Rating: 550hp
Quantity: Sold as 4 pieces /set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

Hurricane 4340 Chrome-Moly Connecting Rods Honda H23 Description

Upgrade your engine's horsepower with a set of Hurricane Speed and Performance H-beam connecting rods. Their 4340 chromoly steel construction provides outstanding strength. Each rod is multi-stage heat-treated: hrc: 34-38, x-rayed, sonic-tested, magnafluxed, 100 percent machined, and shot-peened to stress-relieve the metal, banlance weighthL +/-1g. These rods could assemble ARP 2000 3/8 rod bolts and precision cap alignment sleeves to positively locate each rod cap, silicon bronze bushings for floating pins.

Honda Prelude H23 Rods show:

1. H-beam, providing extended rigidity under vertical load. The best selling option when it comes to forged connecting rods.
2. Double ribbed caps for added strength and better alignment providing bearing caps precision.
3. Bushings in pin end, providing integrity and reliability.



Visit [The Acura and Honda Rod Page](#) for sizes or The Rod Page for general information. You may also find The Rod [FAQ](#) and Rod Info pages helpful.

Set of 4 Hurricane Forged H Beam Honda H23 Connecting Rods Supported Vehicles:

1990-1997 Honda Accord DX
1990-1997 Honda Accord LX
1990-1997 Honda Accord EX
1992-1996 Honda Prelude Si
1995-1995 Honda Prelude SE

Honda H23A Engine



Note: Picture from Wikipedia.