Brand: Hurricane
Engine: Isuzu 4JJ1 3.0L
Part Type: Connecting Rods
Center to Center Length: 158mm/6.221"
Big End Bore Diameter: 56.00mm/2.205"
Big End Width: 33.00mm/1.299"
Small End Bore Diameter: 34.00mm /1.339"
Small End Width: 33.00mm/1.299"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 7/16"
Approximate Connecting Rod Weight: 1070g/piece
Advertised Horsepower Rating: 800hp
Quantity: Sold as 4 pieces /set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

158mm Length Rods For Isuzu Diesel Engine Descripition

Isuzu 158mm Connecting Rods manufactured from the best aircraft quality *4340 chromoly steel* , each rod is featured with an oil groove into pin end to improve pin lubrication, and machined to handle extreme engine loads , tapered on pin end to save weight on the reciprocation end and offer increased clearance for fully boxed pistons, to promote exceptional strength .

Isuzu Performance Conrod Connecting Rod shot-peening effect. we are strict to select steel shot. We only use the cleanest steel shot which has the most suitable size. The result is our connecting rods surface is very bright and smooth. Much more, we make the ISUZU Parts 4JJ1 Connecting Rod shoulder into 3X45° design. We also offer round shoulder and Square shoulder design, for more information, please check our news page : *Hurricane Connecting Rod Shoulder Design*

Hurricane Speed And Performance As a diesel connecting rods manufacturer, All of our Isuzu 158mm forged rods represent the highest quality and are engineered for maximum power. please feel free to *contact us* and inquiry our diesel engine connecting rods sample or ask price.

Isuzu Diesel Truck Car Picture

Note: Photographed by Katherine Hu