

Chevrolet Small Block LS1 LS2 LS6 Connecting Rods Main Sizes

Brand: Hurricane	
Center to Center Length: 155.58mm/6.125"	
Big End Bore Diameter: 56.52mm/2.225"	
Big End Width: 23.88mm/0.940"	
Small End Bore Diameter: 23.56mm /0.928"	
Small End Width: 26.95mm/1.061"	
Beam Style: I-beam	

GM LS1 I beam Connecting Rods Features

Connecting Rod Bolt Diameter	7/16 "
Approximate Connecting Rod Weight	600g
Advertised Horsepower Rating	1600hp
Quantity	Sold as 8 pieces /set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes ,Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes ,available
Custom design	Yes, accept

GM/Chevy LS1 Connecting Rods Description

Hurricane GM LS1 I-beam connecting rods engineered from high tensile 4340 forgings, they can handle high rpm tension forces. All hurricane rods are full finished on CNC advance machinery, [Here is a short introduce for 13 major Process of machining rods](#). This I beam 6.125in connecting rods are shot peened, all the steel shot selected strictly . We only use the cleanest shot which has the most suitable size. That is why our rods` surface is very bright and smooth after shot peening, also with long fatigue life.



One piece and one set LS1 6.125 I beam Connecting rods sample is available, please feel free to [drop us message](#) with your require.







If you prefer H beam connecting rod design for this engine application, [click here to view H-beam CHEVY/GM SBC 6.125" connecting rods](#)

FAQs

1, What is the bolt torque required on rods?

Hurricane LS1 6.125 I beam connecting rods use ARP2000 7/16-1.600" bolts, bolt torque: 95N*M

2, Could you provide logo printing(private label) service on connecting rods?

Yes, please send your logo file to our staff when ordering .

Please [click here for more FAQs.](#)