

Brand: Hurricane
Engine: VW aircooled engine
Part Type: Connecting Rods
Center to Center Length: 136.96mm/5.392"
Big End Bore Diameter: 57.805mm/2.276"
Big End Width: 22.65mm/0.892"
Small End Bore Diameter: 22.005mm /0.866"
Small End Width: 24.70mm/0.972"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8"
Quantity :4pcs/set
Approximate Connecting Rod Weight: 540g/piece
Advertised Horsepower Rating: 800hp
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept


These rods are for VW aircooled engines ,machined from high strength 4340 steel material. Each rod are heat treated, magnafluxed and fully CNC machined for high strength , shot peened and polished for improved fatigue life, and honed to reach accurate sizes . Sold in sets of four pieces, and balanced weight sets +/- 1gram , you can look at the main sizes tolerance in our [official website](#) .

Per part of the rods finished completely , and they are available for genuine ARP2000 connecting rod s bolts . But please kindly note , if you need the rods with genuine ARP bolts when placing order , please contact our staff first to check stock .






Hurricane also supply self-made connecting rods bolts , the tensile strength reach to 211829psi , the test report as below :



TEST REPORT



No. : GZMR120408793
 Date : May. 09, 2012
 Page: 2 of 2

Test Result(s):


Sample description: Metal part

Test item : Tensile test

Test method: With reference to ASTM F606-11a


Test item	Result
The maximum force, F_m (lbf)	16241
Tensile strength R_m (psi)	211829

Test photo:



3/8"-24TX1-1/4"
End of report

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgsgroup.com/terms_and_conditions.htm and for all other further documents subject to Terms and Conditions for Evidence (documents at www.sgsgroup.com/evidence.htm). Attention is drawn to the importance of retaining this document and providing access to it. Any alteration, deletion or modification of this document is deemed null and void. The Company's sole responsibility is to the Client and the document does not constitute a warranty or a representation of the Company's quality or performance under the transaction concerned. The document is issued as full without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Please refer to the test results shown in this test report referring to the test item, tested and such samples are required for 30 days only.



SGS
Société Générale de Surveillance

GZMR 0155923

190-23-62155555 190-23-62155555 190-23-62155555
 中国 · 广州 · 越秀区永平路10号 邮编: 510663 190-23-62155555 190-23-62155555 www.sgsgroup.com
 Member of the SGS Group (SGS SA)



Both bolts has some difference between strength and price , you can view more details in [here](#) or contact out experienced staff directly .