

Brand: Hurricane
Engine: Chevy 7.4L/454 6.5L/396 7.0L/427 6.6L/402
Part Type: Connecting Rods
Center to Center Length: 155.83mm/6.135"
Big End Bore Diameter: 59.047mm/2.325"
Big End Width: 25.170mm/0.991"
Small End Bore Diameter: 25.146mm /0.990"
Small End Width: 28.7mm/1.130"
Beam Style: I-beam
Connecting Rod Bolt Diameter: 7/16"
Quantity :8pcs/set
Approximate Connecting Rod Weight: 720g/piece
Advertised Horsepower Rating: 1200hp
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

4340 I-beam Rods 6.135" Length specs

Free your engine's horsepower on the wings of Hurricane I-beam connecting rods, 4340-certified steel construction provides outstanding strength. Each rod is multi-stage heat-treated, magnafluxed, 100 percent machined, and then shot-peened to stress-relieve the metal.



The rods have precision cap alignment sleeves to positively locate each rod cap, silicon bronze bushings for floating pin models—and are available in stroker models that allow additional cam-to-rod clearance for large stroke combinations.



They could come standard with 190,000 psi rated ARP 8740 and 230,000 psi rated ARP 2000 rod bolts, or 265,000 psi rated ARP L-19 bolts as upgrades. Instructions and rod bolt lubrication are included.



Order the model designed for your vehicle make and engine application, contact us: Marketing@hurricane-rod.com.cn

[All hurricane Chevy series Chrome Moly 4340 Connecting Rods](#), included BBC conrods:
BBC 6.385"

BBC 6.535"
BBC 6.700"
BBC 6.800"
BBC 7.100"

FAQ

A: What is your connecting rod tolerance?

B: Main size: Center to center length: +/- 0.05mm;

Big end bore: + 0.013mm;

Small end bore: + 0.005mm;

Big End width: +/- 0.02mm;

Pin End width: +/- 0.05mm;

No note tolerance: +/- 0.15mm