


Brand: Hurricane
Engine: Chevy Air Cooled
Part Type: Connecting Rods
Center to Center Length: 139.7mm/5.500"
Big End Bore Diameter: 53.97mm /2.125"
Big End Width: 22.65mm/0.8917"
Small End Bore Diameter: 22.mm/0.866"
Small End Width: 24.7mm/0.9724"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8 "
Approximate Connecting Rod Weight: 550g/piece
Advertised Horsepower Rating: 1000hp
Quantity: Sold as 8 pieces /set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

5.500' H Beam Connecting Rods for the Chevy Air Cooled Engine Description

Hurricane's H-Beam rods are a must if you are planning on building an all out performance engine. H-Beam design combines weight savings and high strength thanks to the forged 4340 chromoly construction. Radiused rod caps help to reduce the amount of clearancing required on stroker applications and are sleeved to the rod to eliminate cap shifting. Precision machined rods are magna fluxed and sold in matched weight sets of 8 .



Chevy Air Cooled Forged Conrods Feature:

NEW 4340 Certified Forged Steel Rod

Aluminum QAL10-3-1.5 Bushings

Precision alignment sleeves positively locate the rod cap, eliminating cap shift

Packaged in weight matched sets end to end +/- 1 gram

Mirco-polished and shot peened

Small and Big end bore Honed to use size



Each chevy 5.500 H beam conrods includes Hurricane cap fasteners that are rated at 211,829psi, They conrods can perfectly fits ARP 2000, ARP L19 or ARP625+ bolts and reach 220.000-280.000psi as an upgrade, All of hurricane conrods have been tested by ARP2000 bolts before packing.

Any Needs, please feel free to contact hurricane team: marketing@hurricane-rod.com.cn