

Brand: Hurricane
Engine: Honda D16L
Part Type: Connecting Rods
Center to Center Length: 138.66mm/5.459"
Big End Bore Diameter: 48.01mm/1.890"
Big End Width: 22.66mm/0.892"
Small End Bore Diameter: 19.00mm /0.748"
Small End Width: 18.16mm/0.715"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8"
Quantity :4pcs/set
Approximate Connecting Rod Weight: 469g/piece
Advertised Horsepower Rating: 550hp
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

H-beam High Performance Conrod Connecting Rods for Honda D16L Description

These H-beam connecting rod engineered from high tensile [4340 steel material](#) ,they match to Honda D16L engine , each rod are polished and shot peened to improve fatigue life. Per rod fully finished by advance CNC machine , the surface looks very smooth ,It is hard to see the tool vestige.



Each rod connected by quality dowel sleeve , it is easy to remove beam and cap , and achieve re-assembling . Per rod installed bronze bushings for improved wrist pin life .



One oil hole drilled at the top of small end for enough lubrication for piston , to increase piston fatigue life



Hurricane Honda D16L performance connecting rods fits for:

1988 - 2000 Honda Civic (EX, EX)

1993 - 1997 Honda Civic del Sol (Si, Si)

1988 - 1991 Honda CRX (Si, Si)

Any further question, please don't hesitate to [contact](#) us .