


## 4G63 X beam connecting rods Main Sizes

Brand: Hurricane	
Center to Center Length: 150.00mm/5.906"	
Big End Bore Diameter: 48.00mm/1.890"	
Big End Width: 26.37mm/1.038"	
Small End Bore Diameter: 22mm /0.866"	
Big End Width: 26.37mm/1.038"	
Beam Style: X-beam	

## Connecting Rods Mitsubishi EVO Features

Connecting Rod Bolt Diameter	3/8"
Approximate Connecting Rod Weight	~
Advertised Horsepower Rating	700hp
Quantity	Sold as 4 pieces /set
Material	<a href="#">Forged 4340 steel</a>
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes ,Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes ,available
Custom design	Yes, accept

## Forged Connecting Rods For Mitsubishi EVO 4G63 (2.0L) Description

Hurricane factory makes connecting rods for street engines and most racing applications, making them the preferred choice to professionals. We Follow a strict procedure for each job to ensure a high level of quality is delivered. so our Forged Connecting Rods for Mitsubishi Evo 4G63 (2.0L) are tough and strong.




Those Forged 4340 Steel Connecting Rods for 4G63T Engines are ready for cleaning, inspecting and packing.

**Optional forced pin oiling (rifle drilling) for long wrist pin life**

Rifle Drilled(oiling channel from big end to piston pin), Also referred to as Forced Pin Oiling(FPO), rifle

## Forged 4340 Steel Connecting Rods for 4G63T Engines Main Size



## OTHER CUSTOMERS ALSO BOUGHT

Hurricane Performance Replacement Connecting rods bolts Size: 3/8 x 1.600" inch