

Brand: Hurricane
Engine: Honda Prelude H22 VTEC 2.2L
Part Type: Connecting Rods
Center to Center Length: 143.15mm/5.636"
Big End Bore Diameter: 51.003mm/2.008"
Big End Width: 23.75mm/0.935"
Small End Bore Diameter: 22.015mm /0.8667"
Small End Width: 22mm/0.8661"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8"
Approximate Connecting Rod Weight: 545g/piece
Advertised Horsepower Rating: 550hp
Quantity: Sold as 4 pieces /set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

Honda Prelude H22 H beam Connecting Rods Description

Hurricane finished H-beam race rods fits HONDA Prelude H22 VTEC 2.2L engine. these rods are made from 1-piece **chromoly 4340 steel** forging to ensure maximum strength and durability. Unique H-beam design is substantially stronger and lighter than OEM equipment, allowing your engine to rev quicker and hold up to the punishing demands of high boost applications.



Per rod [shot peened](#) and polished for increased fatigue life, so the rod's surface looks more beautiful. Per h22 rod's specs tolerance controlled with high technical level to meet high quality standard. All Honda 4340 performance H22 H beam rods packaged with 4 pieces per set , and balanced weight sets within +/- 1 gram to keep balance well.





Hurricane new finish honda h22 5.636" H beam connecting rods installed with [Hurricane replacement 3/8 rod bolts](#). Currently we can not offer Original ARP2000 bolts, but if we have cooperation, you can ship original ARP bolts to Hurricane factory for free install.



Please feel free [contact](#) us if you have any further question for this products.