

Nissan Sr20de 136.3mm X-beam Conrods Main Dimensions

Brand: Hurricane	
Center to Center Length: 136.30mm/5.366"	
Big End Bore Diameter: 51.00mm/2.008"	
Big End Width: 22.80mm/0.898"	
Small End Bore Diameter: 22.00mm /0.866"	
Small End Width: 22.80mm/0.898"	
Beam Style: X-beam	

Nissan Sr20de 136.3mm X-beam Conrods Features

Connecting Rod Bolt Diameter	3/8 "
Approximate Connecting Rod Weight	xxx
Advertised Horsepower Rating	600hp
Quantity	Sold as 4 pieces /set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes ,Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes ,available
Custom design	Yes, accept

Additional Description :

- 1). MOQ: 100pcs per model .
- 2). Machined from premium 4340 forged steel forgings .



- 3). Each forging is X-rayed, sonic tested and magnafluxed.
- 4). Fully shot peening to relieve stress and improve fatigue life .
- 5). Processed by advanced CNC machine .
- 6). High quality bronzed bushing installed for floating piston pin.
- 7). Each rods connected by quality dowel sleeves to achieve re-assembling .
- 8). Per rod finished and honed with tight tolerance for high durability .
- 9). Packaged in balanced per set: end to end +/- 1 gram .
- 10). They are fitting with genuine 3/8" ARP bolts.
- 11). X-beam design combines light weight and high strength.

Hurricane Finished X-beam Connecting Rod Picture



Welcome to [contact us](#) if you have any further question !