

Brand: Hurricane  
Engine: Audi VW V8 3.6 & 4.2 Liter  
Part Type: Connecting Rods  
Center to Center Length: 154mm/6.063"  
Big End Bore Diameter: 56.8mm/2.236"  
Big End Width: 20.12mm/0.792"  
Small End Bore Diameter: 21mm /0.827"  
Small End Width: 21.92mm/0.863"  
Beam Style: H-beam  
Connecting Rod Bolt Diameter: 3/8"  
Approximate Connecting Rod Weight: 600g/piece  
Advertised Horsepower Rating: 1000hp  
Quantity: Sold as 8 pieces /set  
Material: Forged 4340 steel  
Connecting Rod Finish: Shot-peened, Polished  
Pin: Bronze wrist pin bushings  
Wrist Pin Style: Floating  
Cap Retention Style: Cap screw  
Weight Matched Set: Yes ,Balanced +/- 1g  
Magnafluxed: Yes  
Private Label: Yes ,available  
Custom design: Yes, accept

The Audi VW V8 3.6 & 4.2 Liter H beam connecting rods 100% **finished** with high quality level at Hurricane factory , they are 8 pieces per set, forged and heat treated with 34-38HRC for improved tensile and yield strength. Extra shot blasting non machined surfaces to reduce the risk of stress fractures and rod failure.





High quality bronze wrist pin bushings are fitted to each rod to increased wear resistance.



For more Audi/VW rods, please [check this page](#), you can also click here to [download Hurricane connecting rods catalog](#).

Hurricane also can make custom connecting rods based on specified dimensions and design , you can fill your specs into our " [Custom Connecting Rod Form](#) " and send to our experienced staff if you have needs. The Process Of Custom Conrods as below :

- 1) received the drawing or sample , then we make quote detail
- 2) if you agree our quote , then we design drawing
- 3) each other confirm the drawing and deal detail
- 4) all confirm finished , 30% deposit required , then we make sample for you to test if necessary
- 5) balance before shipping , then we arrange shipping by your forwarder or our forwarder in time once received payment .

Any question for this product , please feel free [contact](#) us !