

Brand: Hurricane  
Engine: HONDA / ACURA B18C GSR  
Part Type: Connecting Rods  
Center to Center Length: 138mm/5.433"  
Big End Bore Diameter: 48.01mm/1.8902"  
Big End Width: 21.79mm/0.858"  
Small End Bore Diameter: 21.01mm /0.827"  
Small End Width: 21mm/0.8268"  
Beam Style: H-beam  
Connecting Rod Bolt Diameter: 3/8"  
Approximate Connecting Rod Weight: 450g/piece  
Advertised Horsepower Rating: 750hp  
Quantity: Sold as 4 pieces /set  
Material: Forged 4340 steel  
Connecting Rod Finish: Shot-peened, Polished  
Pin: Bronze wrist pin bushings  
Wrist Pin Style: Floating  
Cap Retention Style: Cap screw  
Weight Matched Set: Yes ,Balanced +/- 1g  
Magnafluxed: Yes  
Private Label: Yes, available  
Custom design: Yes, accept

Hurricane made forged conrods are perfectly fits Honda B18C engine, Copy ARP2000 3/8 under head length 1.600" bolts provides seperately. [Click here](#) to check our COPY ARP2000 rod bolt PSI certification.



# Hurricane Honda B18C 138mm Connecting Rods FEATURES

- ☐ Certified 4340 Steel 1-piece forgings for increased strength.
- ☐ Machined with extremely tight tolerances.
- ☐ Bronze Bushings for floating pins.  
Light Weight.
- ☐ Ready for Install.



Custom Conrods are acceptable for different race engine applications and different horsepower requirements. Much more, Hurricane offer private label service for Batch orders.



Hurricane is a performance connecting rods manufacturer located in Chengdu, China. we provide over 50 different connecting rod models and design for Honda Race Cars engines, including Honda B,D,F,H,J,K and L series. Please check [Rods catalog\(.pdf\)](#) to view all Hurricane connecting rods. If you do not find what you want through our catalog, please send your inquiry to: [marketing@hurricane-rod.com.cn](mailto:marketing@hurricane-rod.com.cn) or contact one of our skilled staff directly.

## Acura/Honda Car Picture

