

Honda h22 X beam Steel Connecting Rods Main Sizes

| | |
|------------------------------------------|--|
| Brand: Hurricane | |
| Center to Center Length: 143.15mm/5.636" | |
| Big End Bore Diameter: 51mm/2.008" | |
| Big End Width: 23.75mm/0.935" | |
| Small End Bore Diameter: 22mm /0.866" | |
| Small End Width: 22mm/0.866" | |
| Beam Style: X-beam | |

Connecting Rods for Honda H22 2.2L Engine Features

| | |
|-----------------------------------|-----------------------------------|
| Connecting Rod Bolt Diameter | 3/8 " |
| Approximate Connecting Rod Weight | XXXg |
| Advertised Horsepower Rating | 650hp |
| Quantity | Sold as 4 pieces /set |
| Material | Forged 4340 steel |
| Connecting Rod Finish | Shot-peened, Polished |
| Pin | Bronze wrist pin bushings |
| Wrist Pin Style | Floating |
| Cap Retention Style | Cap screw |
| Weight Matched Set | Yes ,Balanced +/- 1g |
| Magnafluxed | Yes |
| Private Label | Yes ,available |
| Custom design | Yes, accept |

4340 Connecting Rods Honda Prelude & Accord H22 Description

Connecting Rods for Honda H22 2.2L Engine fitted with Doweled Cap for Superior Alignment and Silicone Bronze Pin End Bushes for reliability. honda h22 X beam steel connecting rods are also shot peened and polished for reduced fatigue, 100% CNC Profiling & 100% CNC Drilling & Tapping, these con-rods are made of the highest quality and built to be abused.

Hurricane Honda Prelude H22 forged steel connecting rods Application

| Make | Vehicle Model | Engine |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Honda / Acura | 4th gen Prelude Si VTEC (2WS BB4 & 4WS BB1) 5th gen Prelude SiR (2WS BB6 & 4WS BB8) 5th gen Prelude Type-S and SiR S-Spec (BB6) 6th gen Accord/Torneo Euro-R (CL1) 5th gen Accord SiR Sedan (CD6) 5th gen Accord SiR Coupe (CD8) 5th gen Accord SiR Wagon (CF2) | H22A |
| Honda / Acura | 4th gen Prelude VTEC (BB1) 4th gen Prelude SR-V (BB1) 4th gen VTi-R (BB1) | H22A1 |
| Honda / Acura | Prelude 2.2i VTEC (BB1) | H22A2 |
| Honda / Acura | Honda Accord Coupe SiR | H22A3 |
| Honda / Acura | 5th gen Prelude Base and Type-SH (BB6) 5th gen Prelude Base, Type-SH, and SE (BB6) | H22A4 |
| Honda / Acura | 1997-1998 Prelude 2.2VTi/VTi-S (2WS BB6 & 4WS BB8) | H22A5 |
| Honda / Acura | 1998-2002 Accord Type-R (CH1) | H22A7 |
| Honda / Acura | 1999-2001 Prelude 2.2VTi/VTi-S (2WS BB6 & 4WS BB8) | H22A8 |

OTHER CUSTOMERS ALSO BOUGHT

1. [Honda Prelude H22 VTEC 2.2L 5.636" I beam connecting rods](#)
2. [Forged H beam Honda Prelude H22 connecting rods set, 22mm pin hole](#)
3. [Hurricane Performance Replacement Connecting rods bolts Size: 3/8 x 1.600" inch](#)

Honda Prelude H22 Engine



Note: Picture from Pinterest.