

Subaru EJ20 engine connecting rods Main Sizes

Brand: Hurricane	
Center to Center Length: 130.50mm/5.137"	
Big End Bore Diameter: 54.991mm/2.165"	
Big End Width: 21.34mm/0.840"	
Small End Bore Diameter: 23.012mm /0.906"	
Small End Width: 21.34mm/0.840"	
Beam Style: I-beam	

Subaru 2.0/2.2T WRX 2.5L STI EJ25/EJ20 connecting rods More details

Connecting Rod Bolt Diameter	3/8 "
Approximate Connecting Rod Weight	~
Advertised Horsepower Rating	1000hp
Package	4 pieces per set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes, available
Custom design	Yes, accept

Custom Conrods for Subaru Engine Description

The rods are the go-to when upgrading your Subaru 2.0/2.2T WRX 2.5L STI EJ25/EJ20

Advantages:

- 1.You won't get a better product for this price.
- 2.We put these into engines that make up to 1000HP and have never had one fail.
- 3.They always have finished size pin bushing so you likely won't need any additional machining. Simply install your bearings, check your clearances, and put the power down.

4.All rods are properly shot peened after machining and 100% magnafluxed.

5.They are compatible with all ej20 engines

6.All Hurricane connecting rod sets, are weight matched to ± 1 grams, big end bores are final honed to a tolerance of $\pm .006$ mm.

Custom Connecting Rods



Hurricane Speed and Performance has connecting rods for a variety of applications, including our custom Super Series 4340 forged steel connecting rods, manufactured our specifications with fully CNC machine.

In addition to our Custom forged 4340 steel connecting rods, we have other steel 4140, 5140, aluminum, 300M, titanium rods available from most of the nations leading manufacturers. Call for pricing and availability.

