


Honda H23 Rods Main Sizes

Brand: Hurricane*	
Center to Center Length: 141.50mm/5.571"	
Big End Bore Diameter: 51.01mm/2.008"	
Big End Width: 23.75mm/0.935"	
Small End Bore Diameter: 22.01mm /0.867"	
Small End Width: 23.75mm/0.935"	
Beam Style: I-beam	

Connecting Rod Honda H23/F22 More Details

Connecting Rod Bolt Diameter	3/8 "
Approximate Connecting Rod Weight	~
Advertised Horsepower Rating	800hp
Package	4 pieces per set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes, available
Custom design	Yes, accept

I beam connecting rods for Honda H23 Features

Honda Prelude forged rods are machined from grade tested (X-Ray & Sonic) 4340 steel one piece forging, doweled cap for superior alignment and fitted with silicone bronze pin end bushes. I beam connecting rods for Honda H23 are honed to use size and designed to suit 800 horsepower engines.



Forged 4340 Steel Connecting Rod For Honda Prelude
H23 H23A are fitted with [hurricane 3/8 replacement bolts](#).

Application:

H23A	1992-1996 Ascot Innova 2.3Si-Z
H23A1	4th gen Prelude Si (BB2) 1995 Prelude SE (BB2) 4th gen Prelude SR (BB2) 4th gen Prelude Si (BB2) 1991-1993 Prelude SRS (BB2)
H23A2	4th gen Prelude 2.3i (BB2)
H23A3	1993-1995 Accord 2.3i SR (CC7) 1993-1999 Rover 623 SLi, GSi, and iS
H23A DOHC VTEC	1998-2002 Accord Wagon SiR (CH9) 1998-2002 Accord Wagon AWD (CL2)

Hurricane factory produced lots of connecting rods for Honda engines, if you do not find what you need through our website, please feel free to [contact us](#). Our experianced sales staff is here to assist you and we can accept custom design order.

Package

Hurricane factory could offer following package boxes.

hurricane box



white box



foam box

