

Brand: Hurricane*
Engine: Nissan E15
Part Type: Connecting Rods
Center to Center Length: 137.14mm/5.399"
Big End Bore Diameter: 43.01mm/1.693"
Big End Width: 21.84mm/0.860"
Small End Bore Diameter: 19.01mm /0.748"
Small End Width: 21.84mm/0.860"
Beam Style: H-beam
Connecting Rod Bolt Diameter: 3/8"
Approximate Connecting Rod Weight: ~g per piece
Advertised Horsepower Rating: ~hp
Quantity: Sold as 4 pieces per set
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes, Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes, available
Custom design: Yes, accept

Nissan E15 H beam Forged 4340 Connecting Rods Description

You can [Customs Connecting Rods](#) for your Nissan E15. These H-beam connecting rods are great for up to applications you want. Comes with ARP bolt, Hurricane bolt or OEM bolt.



Hurricane Conrods Features

Hurricane's H-beam connecting rods are made from 4340 steel, x-rayed, magnafluxed, sonic tested, and shot-peened to ensure optimal quality and strength. They are packaged in weight-matched sets that are within +/- 1 gram end to end.

The Hurricane all connecting rods undergo a 1-piece forging process in China and produce well which you can install on your engine directly; making for a cheaper rod that is durable and precise.



Applications:

E15/E15S:

Nissan AD van (VB11)
Nissan Cherry (N12)
Nissan Prairie (M10)[4]
Nissan Pulsar/Cherry/Datsun 310 (N10)
Nissan Pulsar (N12)
Nissan Sentra (B11)
Nissan Sunny (B11)
Nissan S-Cargo

E15ET: Nissan Pulsar ET/EXA/Cherry/Langley GT/Sunny LePrix Turbo

All **Nissan rods** that Hurricane produced like:

1. [Nissan QR25 Rods](#)
2. [Nissan 2.0 SR20DE, SR20DET Rods](#)
3. [Nissan 240SX-KA24DE Rods](#)
4. [Nissan RB30 Rods](#)
5. [Nissan RB26/RB25 Rods](#)
6. [Nissan TB48 Rods](#)

Nissan Sunny B11 Car



Note: Picture from Wikimdedia commons.