

Brand: Hurricane\*  
Engine: Suzuki swift M15A  
Part Type: Connecting Rods  
Center to Center Length: 138.00mm/5.433"  
Big End Bore Diameter: 45.00mm/1.772"  
Big End Width: 23.91mm/0.941"  
Small End Bore Diameter: 20.01mm /0.788"  
Small End Width: 18.90mm/0.744"  
Beam Style: H-beam  
Connecting Rod Bolt Diameter: 3/8"  
Approximate Connecting Rod Weight: 525g/piece  
Advertised Horsepower Rating: 600hp  
Quantity: Sold as 4 pieces /set  
Material: Forged 4340 steel  
Connecting Rod Finish: Shot-peened, Polished  
Pin: Bronze wrist pin bushings  
Wrist Pin Style: Floating  
Cap Retention Style: Cap screw  
Weight Matched Set: Yes ,Balanced +/- 1g  
Magnafluxed: Yes  
Private Label: Yes ,available  
Custom design: Yes, accept

These H Beam connecting rods designed and developed for Suzuki swift M15A engines , engineered from high tensile [4340 forged steel](#) material , high quality H-BEAM design for lighter weight, and all M15A rods are heat treated , magnafluxed, shot peened, fully machined in Hurricane factory for for superior fatigue life and high strength .



Per rod fully machine at [Hurricane CNC center](#) to handle maximum strength .



All big and small end bore honned with advanced honing machine for superior tight tolerance , per dimension inspected at workshop to guarantee high reliability .

In short, if you are looking for a strong rod for your racing Suzuki applications, Hurricane connecting rod will be a suitable one .