

Brand: Hurricane
Engine: VW Scirocco/Jetta/Golf 1.8L/1.8T
Part Type: Connecting Rods
Center to Center Length: 144mm/5.670"
Big End Bore Diameter: 50.60mm/1.992"
Big End Width: 24.89mm/0.980"
Small End Bore Diameter: 20mm /0.787"
Small End Width: 21mm/0.827"
Beam Style: I-beam
Connecting Rod Bolt Diameter: 3/8"
Quantity :4pcs/set
Approximate Connecting Rod Weight: 600g/piece
Advertised Horsepower Rating: 750hp
Material: Forged 4340 steel
Connecting Rod Finish: Shot-peened, Polished
Pin: Bronze wrist pin bushings
Wrist Pin Style: Floating
Cap Retention Style: Cap screw
Weight Matched Set: Yes ,Balanced +/- 1g
Magnafluxed: Yes
Private Label: Yes ,available
Custom design: Yes, accept

VW 1.8T 144x20mm Forged connecting rods Description

Forged **Hurricane customs connecting rod** set for 4-cyl VW/Audi motors with 144mm length and 20mm wrist pin, The small end width is 21.9mm.

Hurricane fully finish all rods with advanced CNC machine in China. Don't accept inferior quality rods machined overseas to unknown tolerances. All tolerances will be noted on drawing when you make order, included:

Main size: Center to center length: +/- 0.05mm;

Big end bore:+ 0.013mm;

Small end bore:+ 0.005mm;

Shoulder width:+/- 0.03mm;

No note tolerance:+/-0.15mm.

These rods engineered from high tensile 4340 steel material , per rod installed with bronzed bushing for floating piston pin . Built with I-beam shape to handly high horsepower , forged with raised caps to reduce stress better .



Per set rods weight matched within 2 gram , and sold as 4 pieces per set.



Hurricane can supply [replacement bolts](#) as well, no moq limits, welcome to [contact](#) us to learn about more details .



If you have more questions, you could find on [FAQ](#), or [leave an message](#) .