

Connecting rods for Honda S2000 F20C Main Sizes

Brand: Hurricane	
Center to Center Length: 152.98mm/6.023"	
Big End Bore Diameter: 51mm/2.008"	
Big End Width: 23.85mm/0.939"	
Small End Bore Diameter: 23mm/0.906"	
Small End Width: 22mm/0.866"	
Beam Style: I-beam	

Connecting Rods Set Honda S2000 AP1 F20C Features

Connecting Rod Bolt Diameter	3/8"
Approximate Connecting Rod Weight	xxxx
Advertised Horsepower Rating	800hp
Quantity	Sold as 4 pieces /set
Material	Forged 4340 steel
Connecting Rod Finish	Shot-peened, Polished
Pin	Bronze wrist pin bushings
Wrist Pin Style	Floating
Cap Retention Style	Cap screw
Weight Matched Set	Yes ,Balanced +/- 1g
Magnafluxed	Yes
Private Label	Yes ,available
Custom design	Yes, accept

Honda S2000 F20C I Beam Connecting Rod Description

All hurricane factory performance connecting rods are manufactured from 4340 high tensile steel and are designed for high performance and extreme durability. Honda S2000 F20C I Beam Connecting Rod can reach 800 horsepower. Honda connecting rods for F20C engine are shot peened to relieve stress from the material and multi-stage heat treated to increase rigidity. The tight tolerances in the production process, ensure a perfect fitment. Each rod includes Hurricane 3/8 cap fasteners that are rated at 211,829psi,

Connecting Rods Set Honda S2000 AP1 F20C are perfectly honed big/small ends and balance weighted to + / - 1 gram.



Connecting rods for Honda S2000 F20C are packaged with rust proof paper, then put into plastic bag and seal

Fitting Info

Make	Honda / Acura
Vehicle	S2000 00-03 AP1
Engine	F20C

Honda S2000 Race Car



Note: Picture from Pinterest.