

Brand: Hurricane  
Engine: Toyota LEXUS 1/2/3UZFE  
Part Type: Connecting Rods  
Center to Center Length: 146mm/5.748"  
Big End Bore Diameter: 55mm/2.165"  
Big End Width: 22.85mm/0.900"  
Small End Bore Diameter: 22.02mm /0.867"  
Small End Width: 21mm/0.827"  
Beam Style: H-beam  
Connecting Rod Bolt Diameter: 3/8"  
Approximate Connecting Rod Weight: 575g/piece  
Advertised Horsepower Rating: 1200hp  
Quantity: Sold as 8 pieces /set  
Material: Forged 4340 steel  
Connecting Rod Finish: Shot-peened, Polished  
Pin: Bronze wrist pin bushings  
Wrist Pin Style: Floating  
Cap Retention Style: Cap screw  
Weight Matched Set: Yes ,Balanced +/- 1g  
Magnafluxed: Yes  
Private Label: Yes ,available  
Custom design: Yes, accept

## **Lexus 1UZFE, 2UZFE and 3UZFE rod description**

Hurricane 4340 Chrome Moly Connecting Rods for LEXUS 1/2/3UZFE engines are precision forged 4340 EN24 aircraft quality steel,vacuum degased to remove impurities.



All surfaces are shot blasted and micro-polished before finishing machining. It it relieve stress and improved fatigue life.



Finally, package with weight tolerance less than  $\pm 1g$  in one set, which 8 pieces per set.

If you are interested with more information, you can find the appearance compare pictures at [News Page](#).

## FAQ

A: What is the bolt torque required on rods?

B: ARP2000 5/16-1.500" 45N\*m  
ARP2000 3/8 -1.600" 75N\*m  
ARP2000 7/16-1.600" 95N\*m

