

Brand: Hurricane  
Engine: Honda K20A3  
Part Type: Connecting Rods  
Center to Center Length: 138.51mm/5.453"  
Big End Bore Diameter: 48.01mm/1.890"  
Big End Width: 19.81mm/0.780"  
Small End Bore Diameter: 22.02mm /0.867"  
Small End Width: 22.86mm/0.900"  
Beam Style: H-beam  
Connecting Rod Bolt Diameter: 3/8"  
Quantity: 4 pieces per set  
Approximate Connecting Rod Weight: 460g/piece  
Advertised Horsepower Rating: 750hp  
Material: Forged 4340 steel  
Connecting Rod Finish: Shot-peened, Polished  
Pin: Bronze wrist pin bushings  
Wrist Pin Style: Floating  
Cap Retention Style: Cap screw  
Weight Matched Set: Yes ,Balanced +/- 1g  
Magnafluxed: Yes  
Private Label: Yes ,available  
Custom design: Yes, accept

## Honda K20A3 5.453" forged connecting rods Description

These Honda K20A3 forged connecting rods are created from high strength 4340 (EN24) steel and machined to accurate tolerances, it highly suits for 750hp performance engine , and all the surfaces are machined by special CNC machine , so it looks smooth and beautiful.

H-Beam Rods Honda K20 Round shoulder design improving clearance. For other design, please click [Hurricane Connecting Rod Shoulder Design](#)



Hurricane produce connecting rods for various Honda performance engines , include [HONDA Prelude H22 VTEC 2.2L](#), [Honda D16A](#), [Honda F23 Accord 2.0](#) , [Honda Acura Integra GSR 1.8 VTEC B18C](#), [Honda B16A VTEC 1.6L](#), [Honda F20C/S2000](#) , [Honda L15A FIT/JAZZ](#) , [HONDA / ACURA J35](#) , [Honda K24](#) , [Honda F20B](#) , [Honda B18](#) etc . If you can not find the model or the design you need , please don't hesitate to [contact](#) us , custom conrod can be made as your requirements .

For bolts, Hurricane usually supply Copy ARP2000 bolts which can hold 200000-211829 psi , but the Copy bolts without "ARP" font , some pictures attached for reference as below :



3/8" and 7/16"

5/16"



Please contact our experienced staff to learn about more details if you are interested in bolts .